

## Uncompressed 4K Decoder with Dante and Icron USB

Z4KFXS-DAU is an HDMI 2.0 AVoIP Decoder that is part of the ZyPer4k product line. It supports IP streaming over 10Gbit fiber up to 4KP60 4:4:4 resolution with embedded Dante audio support and HDCP 2.3 encryption at zero-frame latency. Configurable Icron USB allows support between any USB enabled ZyPer4K device. Video compatible with any ZyPer4K AVoIP Encoder. AC power supply is included but other cables are not.

### Z4KFXS-DAU



Audio Out port



10Gb Ethernet port

1 Gb Utility port

USB port

Serial (RS232) Output

## What's in the box?

- ZyPer4K-XS Decoder Fiber
- Power Supply

# ZyPer4K-XS

Product Number: Z4KFXS-DAU

ZyPer4K-XS Decoder	Information
Video	HDMI 2.0 with HDCP pass-through
Audio (Digital)	Encoded audio formats and linear PCM up to 8 channels
Audio (Analog)	Balance Stereo (5-pin phoenix) Output
Serial (RS232)	3-pin phoenix
USB	Single USB 2.0 (USB - A connector)
Ethernet	10 Gb for Video/Audio/Control with 1 Gb Utility
Other Specifications	ZyPer4K-XS Decoder Fiber
Formats	Supports all major VESA resolutions and variations including full HDMI 2.0 support: VGA: 640x480 (4:3)                      XGA: 1024x768 (4:3) SXGA: 1280x1024 (5:4)                SXGA+: 1440x1080 (4:3) 1080p/i: 1920x1080 (16:9)        Ultra HD: 3840x2160 (16:9) SVGA: 800x600 (4:3)                    HDTV: 1280x720 (16:9) WXGA: 1366x768 (16:9)                UXGA: 1600x1200 (4:3) QXGA: 2048x1536 (4:3)                4K: 4096x2160 (17:9)  Custom resolutions are supported at pixel clock rates up to 600 MHz
Video Other	Color depth: 24 bit, 30 bit, 36 bit, 48 bit
Video Wall and Multiview	Video Wall up to 15x15. Multiview with up to 19 sources
Signal transmission distance	Multimode fiber optic line: 300m   single mode fiber optic line: 10km
Copy Protection/Security	HDCP 2.2, AES-128 Encryption, 802.1X compatible
Power input (locking connector)	12V DC
Power	Approximately 8 watts
Dimensions (L x W x H) / Weight	7.8 in (199mm) x 5.4 in (136mm) x 1.9 in (48mm), 35.2 oz (1000g)
Temperature	Operating temperature: 32 F to 104 F <0 C to +40 C> Storage temperature: -4 F to +176 F <-20 C to +80 C>
Humidity	Operating/ Storage: 20% to 90% (Non-Condensing)
Accessories	Description
Z4KSFP10G85-3M	ZyPer4K, Fiber Optic Transceiver, SFP+ 10Gbps 850nm MMF 300m
Z4KSFP10G31-10K	ZyPer4K, Fiber Optic Transceiver, SFP+ 10Gbps 1310nm SMF 10km
Z4KPWRCTR12	ZyPer 12V Power Center for use with up to 8 ZyPer Encoder/Decoders (all models). 1 RU. Includes rack ears, 8 3-foot locking 12V DC power cables, AC power cord.
Z4KVESABRK	ZyPer4K VESA Bracket is a custom wall/desk/display mount bracket for ZyPer4K. Supports standard VESA parameters for mounting directly to rear of a display. 100x100, 100x200 and 200x200 VESA hole mounts are supported.

## ENTIRE PRODUCT LINE:

Z4KDECC3XS  
Z4KDECF3XS  
Z4KENCC3XS  
Z4KENCF3XS

Z4KC2XS-E  
Z4KC2XS-EAU  
Z4KF2XS-E  
Z4KF2XS-EAU

Z4KC2XS-D  
Z4KC2XS-DAU  
Z4KF2XS-D  
Z4KF2XS-DAU

## ZYPER4K-XS WALL PLATES:

Z4KDECC3XS-WPEU-I  
Z4KDECC3XS-WPEU  
Z4KENCC3XS-WPUS-I  
Z4KENCC3XS-WPUS